

HUNAN BALING STEEL CO.,LTD

Casing Pipe Dimensions and Weight Chart for API round thread and buttress thread

Labels		Dimensions					Calculated mass C				
Size label	Weight label (lb/ft)	Outside diameter D (in)	Nominal linear mass T&C (lb/ft)	Wall thickness t (in)	Inside diameter d (in)	Drift diameter (in)	Plain-end mass (lb/ft)	Round thread Short (lb)	Round thread Long (lb)	Buttress thread RC (lb)	Buttress thread SCC (lb)
4 1/2	9.50	4.50	9.50	0.21	4.09	3.97	9.41	4.20			
4 1/2	10.50	4.50	10.50	0.22	4.05	3.93	10.24	3.80		5.00	2.56
4 1/2	11.60	4.50	11.60	0.25	4.00	3.88	11.36	3.40	3.80	4.60	2.16
4 1/2	13.50	4.50	13.50	0.29	3.92	3.80	13.05		3.20	4.00	1.56
4 1/2	15.10	4.50	15.10	0.34	3.83	3.70	15.00		2.80	3.20	0.76
5	11.50	5.00	11.50	0.22	4.56	4.44	11.24	5.40			
5	13.00	5.00	13.00	0.25	4.49	4.37	12.84	4.80	5.80	6.60	2.42
5	15.00	5.00	15.00	0.30	4.41	4.28	14.88	4.20	5.20	5.80	1.62
5	18.00	5.00	18.00	0.36	4.28	4.15	17.95		4.20	4.40	0.22
5	21.40	5.00	21.40	0.44	4.13	4.00	21.32		2.95	2.46	-1.72
5	23.20	5.00	23.20	0.48	4.04	3.92	23.11		2.30	2.05	-2.09
5	24.10	5.00	24.10	0.50	4.00	3.88	24.05		1.95	1.24	-2.94
5 1/2	14.00	5.50	14.00	0.24	5.02	4.89	13.71	5.40			
5 1/2	15.50	5.50	15.50	0.28	4.95	4.83	15.36	4.80	5.80	6.40	2.10
5 1/2	17.00	5.50	17.00	0.30	4.89	4.77	16.89	4.40	5.40	5.80	1.50
5 1/2	20.00	5.50	20.00	0.36	4.78	4.65	19.83		4.40	4.60	0.30
5 1/2	23.00	5.50	23.00	0.42	4.67	4.55	22.56		3.20	3.40	0.90
5 1/2	26.80	5.50	26.80	0.50	4.50	4.38	26.72				
5 1/2	29.70	5.50	29.70	0.56	4.38	4.25	29.67				
5 1/2	32.60	5.50	32.60	0.63	4.25	4.13	32.57				
5 1/2	35.30	5.50	35.30	0.69	4.13	4.00	35.35				
5 1/2	38.00	5.50	38.00	0.75	4.00	3.88	38.08				
5 1/2	40.50	5.50	40.50	0.81	3.88	3.75	40.69				
5 1/2	43.10	5.50	43.10	0.88	3.75	3.63	43.26				
6 5/8	20.00	6.63	20.00	0.29	6.05	5.92	19.51	11.00	13.60	14.40	2.38
6 5/8	24.00	6.63	24.00	0.35	5.92	5.80	23.60	9.60	12.00	12.60	0.58
6 5/8	28.00	6.63	28.00	0.42	5.79	5.67	27.67		10.20	10.60	-1.42
6 5/8	32.00	6.63	32.00	0.48	5.68	5.55	31.23		8.80	9.00	-3.02
7	17.00	7.00	17.00	0.23	6.54	6.41	16.72	10.00			
7	20.00	7.00	20.00	0.27	6.46	6.33	19.56	9.40			
7	23.00	7.00	23.00	0.32	6.37	6.25	22.65	8.00	10.40	11.00	1.60
7	23.00	7.00	23.00	0.32	6.37	6.24	22.65	8.00	10.40	11.00	1.60
7	26.00	7.00	26.00	0.36	6.28	6.15	25.69	7.20	9.40	9.60	0.20
7	29.00	7.00	29.00	0.41	6.18	6.06	28.75		8.00	8.20	1.20
7	32.00	7.00	32.00	0.45	6.09	6.00	31.70		6.60	6.80	2.60
7	32.00	7.00	32.00	0.45	6.09	5.97	31.70		6.60	6.80	2.60
7	35.00	7.00	35.00	0.50	6.00	5.88	34.61		5.60	5.60	3.80
7	38.00	7.00	38.00	0.54	5.92	5.80	37.29		4.40	4.20	5.20
7	42.70	7.00	42.70	0.63	5.75	5.63	42.59				
7	46.40	7.00	46.40	0.69	5.63	5.50	46.36				
7	50.10	7.00	50.10	0.75	5.50	5.38	50.11				
7	53.60	7.00	53.60	0.81	5.38	5.25	53.71				
7	57.10	7.00	57.10	0.88	5.25	5.13	57.29				
7 5/8	24.00	7.63	24.00	0.30	7.03	6.90	23.49	15.80			
7 5/8	26.40	7.63	26.40	0.33	6.97	6.84	25.59	15.20	19.00	20.60	6.21
7 5/8	29.70	7.63	29.70	0.38	6.88	6.75	29.06		17.40	18.80	4.41
7 5/8	33.70	7.63	33.70	0.43	6.77	6.64	33.07		15.80	17.00	2.61
7 5/8	39.00	7.63	39.00	0.50	6.63	6.50	38.08		13.60	14.60	0.21
7 5/8	42.80	7.63	42.80	0.56	6.50	6.38	42.43		12.01	11.39	-3.01
7 5/8	45.30	7.63	45.30	0.60	6.44	6.31	44.71		11.04	11.04	-3.36
7 5/8	47.10	7.63	47.10	0.63	6.38	6.25	46.77		10.16	9.23	-5.17
7 5/8	51.20	7.63	51.20	0.69	6.25	6.13	50.95				
7 5/8	55.30	7.63	55.30	0.75	6.13	6.00	55.12				
7 3/4	46.10	7.75	46.10	0.60	6.56	6.50	45.51				
7 3/4	46.10	7.75	46.10	0.60	6.56	6.44	45.51				
8 5/8	24.00	8.63	24.00	0.26	8.10	7.97	23.60	23.60			
8 5/8	28.00	8.63	28.00	0.30	8.02	7.89	27.04	22.20			
8 5/8	32.00	8.63	32.00	0.35	7.92	7.88	31.13	20.80	27.60	28.30	6.03
8 5/8	32.00	8.63	32.00	0.35	7.92	7.80	31.13	20.80	27.60	28.20	6.03
8 5/8	36.00	8.63	36.00	0.40	7.83	7.70	35.17	19.40	25.60	26.20	4.03
8 5/8	40.00	8.63	40.00	0.45	7.73	7.63	39.33		23.80	24.20	2.03
8 5/8	40.00	8.63	40.00	0.45	7.73	7.60	39.33		23.80	24.20	2.03
8 5/8	44.00	8.63	44.00	0.50	7.63	7.50	43.43		21.80	22.20	0.03
8 5/8	49.00	8.63	49.00	0.56	7.51	7.29	48.04		19.60	19.80	-2.37
9 5/8	32.30	9.63	32.30	0.31	9.00	8.85	31.06	24.40			
9 5/8	36.00	9.63	36.00	0.35	8.92	8.88	34.89	23.00	32.00	31.00	6.48
9 5/8	40.00	9.63	40.00	0.40	8.84	8.75	38.97	21.40	30.00	29.00	4.48
9 5/8	40.00	9.63	40.00	0.40	8.84	8.68	38.97	21.40	30.00	29.00	4.48
9 5/8	43.50	9.63	43.50	0.44	8.76	8.60	42.73		28.20	27.20	2.68
9 5/8	47.00	9.63	47.00	0.47	8.68	8.53	46.18		26.60	25.60	1.08
9 5/8	53.50	9.63	53.50	0.55	8.54	8.50	52.90		23.40	22.40	-2.12
9 5/8	53.50	9.63	53.50	0.55	8.54	8.38	52.90		23.40	22.40	-2.12
9 5/8	58.40	9.63	58.40	0.60	8.44	8.38	57.44		21.50	20.13	-4.40
9 5/8	58.40	9.63	58.40	0.60	8.44	8.28	57.44		21.50	20.13	-4.40
9 5/8	59.40	9.63	59.40	0.61	8.41	8.25	58.70				
9 5/8	64.90	9.63	64.90	0.67	8.28	8.13	64.32				
9 5/8	70.30	9.63	70.30	0.73	8.16	8.00	69.76				
9 5/8	75.60	9.63	75.60	0.80	8.03	7.88	75.21				
10 3/4	32.75	10.75	32.75	0.28	10.19	10.04	31.23	29.00			
10 3/4	40.50	10.75	40.50	0.35	10.05	9.89	38.91	26.40		34.40	7.21
10 3/4	45.50	10.75	45.50	0.40	9.95	9.88	44.26	24.40		31.80	4.61
10 3/4	45.50	10.75	45.50	0.40	9.95	9.79	44.26	24.40		31.80	4.61
10 3/4	51.00	10.75	51.00	0.45	9.85	9.69	49.55	22.60		29.40	2.21
10 3/4	55.50	10.75	55.50	0.50	9.76	9.63	54.26	20.80		27.00	-0.19
10 3/4	55.50	10.75	55.50	0.50	9.76	9.60	54.26	20.80		27.00	-0.19

Casing Pipe Dimensions and Weight Chart for API round thread and buttress thread

Labels		Dimensions					Calculated mass C				
Size label	Weight label (lb/ft)	Outside diameter D (in)	Nominal linear mass T&C (lb/ft)	Wall thickness t (in)	Inside diameter d (in)	Drift diameter (in)	Plain-end mass (lb/ft)	Round thread Short (lb)	Round thread Long (lb)	Buttress thread RC (lb)	Buttress thread SCC (lb)
10 3/4	60.70	10.75	60.70	0.55	9.66	9.50	59.45	18.80		24.40	
10 3/4	65.70	10.75	65.70	0.60	9.56	9.40	64.59	16.80		22.00	
10 3/4	73.20	10.75	73.20	0.67	9.41	9.25	72.40				
10 3/4	79.20	10.75	79.20	0.73	9.28	9.13	78.59				
10 3/4	85.30	10.75	85.30	0.80	9.16	9.00	84.80				
11 3/4	42.00	11.75	42.00	0.33	11.08	11.00	40.64	29.60			
11 3/4	42.00	11.75	42.00	0.33	11.08	10.93	40.64	29.60			
11 3/4	47.00	11.75	47.00	0.38	11.00	10.84	45.60	27.60		35.80	
11 3/4	54.00	11.75	54.00	0.44	10.88	10.72	52.62	25.00		32.40	
11 3/4	60.00	11.75	60.00	0.49	10.77	10.63	58.87	22.60		29.60	
11 3/4	60.00	11.75	60.00	0.49	10.77	10.62	58.87	22.60		29.60	
11 3/4	65.00	11.75	65.00	0.53	10.68	10.63	64.03				
11 3/4	65.00	11.75	65.00	0.53	10.68	10.63	64.03				
11 3/4	71.00	11.75	71.00	0.58	10.59	10.43	69.48				
13 3/8	48.00	13.38	48.00	0.33	12.72	12.56	46.02	33.20			
13 3/8	54.50	13.38	54.50	0.38	12.62	12.46	52.79	30.80		40.20	
13 3/8	61.00	13.38	61.00	0.43	12.52	12.36	59.50	28.40		36.80	
13 3/8	68.00	13.38	68.00	0.48	12.42	12.26	66.17	25.80		33.60	
13 3/8	72.00	13.38	72.00	0.51	12.35	12.25	70.67	24.20		31.60	
13 3/8	72.00	13.38	72.00	0.51	12.35	12.19	70.67	24.20		31.60	
16	65.00	16.00	65.00	0.38	15.25	15.06	62.64	42.60			
16	75.00	16.00	75.00	0.44	15.12	14.94	72.86	38.20		45.60	
16	84.00	16.00	84.00	0.50	15.01	14.82	82.05	34.20		39.60	
16	109.00	16.00	109.00	0.66	14.69	14.50	107.60				
18 5/8	87.50	18.63	87.50	0.44	17.76	17.57	84.59	73.60		86.40	
20	94.00	20.00	94.00	0.44	19.12	18.94	91.59	47.00	61.20	54.80	
20	106.50	20.00	106.50	0.50	19.00	18.81	104.23	41.60	54.80	48.40	
20	133.00	20.00	133.00	0.64	18.73	18.54	131.45	30.00	40.60	35.20	

For more info please visit: <https://octgcasing.com/>

HUNAN BALING STEEL CO.,LTD

Casing Pipe Dimensions and Weight Chart for API round thread and buttress thread- Metric Conversion

Labels		Dimensions					Calculated mass C				
Size label	Weight label (lb/ft)	Outside diameter D (mm)	Nominal linear mass T&C (kg/m)	Wall thickness t (mm)	Inside diameter d (mm)	Drift diameter (mm)	Plain-end mass (kg/m)	Round thread Short (kg)	Round thread Long (kg)	Buttress thread RC (kg)	Buttress thread SCC (kg)
4 1/2	9.50	114.30	14.14	5.21	103.89	100.71	14.00	1.91			
4 1/2	10.50	114.30	15.63	5.69	102.92	99.75	15.24	1.72		2.27	1.16
4 1/2	11.60	114.30	17.26	6.35	101.60	98.43	16.91	1.54	1.72	2.09	0.98
4 1/2	13.50	114.30	20.09	7.37	99.57	96.39	19.42		1.45	1.81	0.71
4 1/2	15.10	114.30	22.47	8.56	97.18	94.01	22.32		1.27	1.45	0.34
5	11.50	127.00	17.11	5.59	115.82	112.65	16.73	2.45			
5	13.00	127.00	19.35	6.43	114.15	110.97	19.11	2.18	2.63	2.99	1.10
5	15.00	127.00	22.32	7.52	111.96	108.79	22.14	1.91	2.36	2.63	0.73
5	18.00	127.00	26.79	9.19	108.61	105.44	26.71		1.91	2.00	0.10
5	21.40	127.00	31.85	11.10	104.80	101.63	31.73		1.34	1.12	-0.78
5	23.20	127.00	34.53	12.14	102.72	99.54	34.39		1.04	0.93	-0.95
5	24.10	127.00	35.86	12.70	101.60	98.43	35.79		0.88	0.56	-1.33
5 1/2	14.00	139.70	20.83	6.20	127.38	124.13	20.40	2.45			
5 1/2	15.50	139.70	23.07	6.99	125.73	122.56	22.86	2.18	2.63	2.90	0.95
5 1/2	17.00	139.70	25.30	7.72	124.26	121.08	25.14	2.00	2.45	2.63	0.68
5 1/2	20.00	139.70	29.76	9.17	121.36	118.19	29.51		2.00	2.09	0.14
5 1/2	23.00	139.70	34.23	10.54	118.62	115.44	33.57		1.45	1.54	0.41
5 1/2	26.80	139.70	39.88	12.70	114.30	111.13	39.76				
5 1/2	29.70	139.70	44.20	14.27	111.15	107.98	44.15				
5 1/2	32.60	139.70	48.51	15.88	107.95	104.78	48.47				
5 1/2	35.30	139.70	52.53	17.45	104.80	101.63	52.61				
5 1/2	38.00	139.70	56.55	19.05	101.60	98.43	56.67				
5 1/2	40.50	139.70	60.27	20.62	98.45	95.28	60.55				
5 1/2	43.10	139.70	64.14	22.23	95.25	92.08	64.38				
6 5/8	20.00	168.28	29.76	7.32	153.64	150.47	29.03	4.99	6.17	6.53	1.08
6 5/8	24.00	168.28	35.72	8.94	150.39	147.22	35.12	4.35	5.44	5.72	0.26
6 5/8	28.00	168.28	41.67	10.59	147.09	143.92	41.18		4.63	4.81	-0.64
6 5/8	32.00	168.28	47.62	12.07	144.15	140.97	46.48		3.99	4.08	-1.37
7	17.00	177.80	25.30	5.87	166.07	162.89	24.88	4.54			
7	20.00	177.80	29.76	6.91	163.98	160.81	29.11	4.26			
7	23.00	177.80	34.23	8.05	161.70	158.75	33.71	3.63	4.72	4.99	0.73
7	23.00	177.80	34.23	8.05	161.70	158.52	33.71	3.63	4.72	4.99	0.73
7	26.00	177.80	38.69	9.19	159.41	156.24	38.23	3.27	4.26	4.35	0.09
7	29.00	177.80	43.16	10.36	157.07	153.90	42.78		3.63	3.72	0.54
7	32.00	177.80	47.62	11.51	154.79	152.40	47.17		2.99	3.08	1.18
7	32.00	177.80	47.62	11.51	154.79	151.61	47.17		2.99	3.08	1.18
7	35.00	177.80	52.09	12.65	152.50	149.33	51.51		2.54	2.54	1.72
7	38.00	177.80	56.55	13.72	150.37	147.19	55.49		2.00	1.91	2.36
7	42.70	177.80	63.54	15.88	146.05	142.88	63.38				
7	46.40	177.80	69.05	17.45	142.88	139.70	68.99				
7	50.10	177.80	74.56	19.05	139.70	136.53	74.57				
7	53.60	177.80	79.77	20.62	136.55	133.38	79.93				
7	57.10	177.80	84.97	22.23	133.35	130.18	85.26				
7 5/8	24.00	193.68	35.72	7.62	178.44	175.26	34.96	7.17			
7 5/8	26.40	193.68	39.29	8.33	177.01	173.84	38.08	6.89	8.62	9.34	2.82
7 5/8	29.70	193.68	44.20	9.53	174.63	171.45	43.25		7.89	8.53	2.00
7 5/8	33.70	193.68	50.15	10.92	171.83	168.66	49.21		7.17	7.71	1.18
7 5/8	39.00	193.68	58.04	12.70	168.28	165.10	56.67		6.17	6.62	0.10
7 5/8	42.80	193.68	63.69	14.27	165.13	161.95	63.14		5.45	5.17	-1.37
7 5/8	45.30	193.68	67.41	15.11	163.45	160.27	66.54		5.01	5.01	-1.52
7 5/8	47.10	193.68	70.09	15.88	161.93	158.75	69.60		4.61	4.19	-2.35
7 5/8	51.20	193.68	76.19	17.45	158.78	155.60	75.82				
7 5/8	55.30	193.68	82.30	19.05	155.58	152.40	82.03				
7 3/4	46.10	196.85	68.60	15.11	166.62	165.10	67.73				
7 3/4	46.10	196.85	68.60	15.11	166.62	163.45	67.73				
8 5/8	24.00	219.08	35.72	6.71	205.66	202.49	35.12	10.70			
8 5/8	28.00	219.08	41.67	7.72	203.63	200.46	40.24	10.07			
8 5/8	32.00	219.08	47.62	8.94	201.19	200.03	46.33	9.43	12.52	12.84	2.74
8 5/8	32.00	219.08	47.62	8.94	201.19	198.02	46.33	9.43	12.52	12.79	2.74
8 5/8	36.00	219.08	53.57	10.16	198.76	195.58	52.34	8.80	11.61	11.88	1.83
8 5/8	40.00	219.08	59.53	11.43	196.22	193.68	58.53		10.80	10.98	0.92
8 5/8	40.00	219.08	59.53	11.43	196.22	193.04	58.53		10.80	10.98	0.92
8 5/8	44.00	219.08	65.48	12.70	193.68	190.50	64.63		9.89	10.07	0.01
8 5/8	49.00	219.08	72.92	14.15	190.78	185.06	71.49		8.89	8.98	-1.08
9 5/8	32.30	244.48	48.07	7.92	228.63	224.66	46.22	11.07			
9 5/8	36.00	244.48	53.57	8.94	226.59	225.45	51.92	10.43	14.51	14.06	2.94
9 5/8	40.00	244.48	59.53	10.03	224.41	222.25	57.99	9.71	13.61	13.15	2.03
9 5/8	40.00	244.48	59.53	10.03	224.41	220.45	57.99	9.71	13.61	13.15	2.03
9 5/8	43.50	244.48	64.74	11.05	222.38	218.41	63.59		12.79	12.34	1.22
9 5/8	47.00	244.48	69.94	11.99	220.50	216.54	68.72		12.07	11.61	0.49
9 5/8	53.50	244.48	79.62	13.84	216.79	215.90	78.72		10.61	10.16	-0.96
9 5/8	53.50	244.48	79.62	13.84	216.79	212.83	78.72		10.61	10.16	-0.96
9 5/8	58.40	244.48	86.91	15.11	214.25	212.73	85.48		9.75	9.13	-2.00
9 5/8	58.40	244.48	86.91	15.11	214.25	210.29	85.48		9.75	9.13	-2.00
9 5/8	59.40	244.48	88.40	15.47	213.54	209.58	87.36				
9 5/8	64.90	244.48	96.58	17.07	210.34	206.38	95.72				
9 5/8	70.30	244.48	104.62	18.64	207.19	203.23	103.81				
9 5/8	75.60	244.48	112.51	20.24	203.99	200.03	111.92				
10 3/4	32.75	273.05	48.74	7.09	258.88	254.91	46.48	13.15			
10 3/4	40.50	273.05	60.27	8.89	255.27	251.31	57.90	11.97		15.60	3.27
10 3/4	45.50	273.05	67.71	10.16	252.73	250.83	65.87	11.07		14.42	2.09
10 3/4	45.50	273.05	67.71	10.16	252.73	248.77	65.87	11.07		14.42	2.09
10 3/4	51.00	273.05	75.90	11.43	250.19	246.23	73.74	10.25		13.34	1.00
10 3/4	55.50	273.05	82.59	12.57	247.90	244.48	80.75	9.43		12.25	-0.09
10 3/4	55.50	273.05	82.59	12.57	247.90	243.94	80.75	9.43		12.25	-0.09
10 3/4	60.70	273.05	90.33	13.84	245.36	241.40	88.47	8.53		11.07	
10 3/4	65.70	273.05	97.77	15.11	242.82	238.86	96.12	7.62		9.98	

Casing Pipe Dimensions and Weight Chart for API round thread and buttress thread- Metric Conversion

Labels		Dimensions					Calculated mass C				
Size label	Weight label (lb/ft)	Outside diameter D (mm)	Nominal linear mass T&C (kg/m)	Wall thickness t (mm)	Inside diameter d (mm)	Drift diameter (mm)	Plain-end mass (kg/m)	Round thread Short (kg)	Round thread Long (kg)	Buttress thread RC (kg)	Buttress thread SCC (kg)
10 3/4	73.20	273.05	108.93	17.07	238.91	234.95	107.74				
10 3/4	79.20	273.05	117.86	18.64	235.76	231.80	116.95				
10 3/4	85.30	273.05	126.94	20.24	232.56	228.60	126.20				
11 3/4	42.00	298.45	62.50	8.46	281.53	279.40	60.48	13.43			
11 3/4	42.00	298.45	62.50	8.46	281.53	277.57	60.48	13.43			
11 3/4	47.00	298.45	69.94	9.53	279.40	275.44	67.86	12.52		16.24	
11 3/4	54.00	298.45	80.36	11.05	276.35	272.39	78.31	11.34		14.70	
11 3/4	60.00	298.45	89.29	12.42	273.61	269.88	87.61	10.25		13.43	
11 3/4	60.00	298.45	89.29	12.42	273.61	269.65	87.61	10.25		13.43	
11 3/4	65.00	298.45	96.73	13.56	271.32	269.88	95.29				
11 3/4	65.00	298.45	96.73	13.56	271.32	269.88	95.29				
11 3/4	71.00	298.45	105.66	14.78	268.88	264.92	103.40				
13 3/8	48.00	339.73	71.43	8.38	322.96	319.00	68.49	15.06			
13 3/8	54.50	339.73	81.10	9.65	320.42	316.46	78.56	13.97		18.23	
13 3/8	61.00	339.73	90.78	10.92	317.88	313.92	88.55	12.88		16.69	
13 3/8	68.00	339.73	101.20	12.19	315.34	311.38	98.47	11.70		15.24	
13 3/8	72.00	339.73	107.15	13.06	313.61	311.15	105.17	10.98		14.33	
13 3/8	72.00	339.73	107.15	13.06	313.61	309.65	105.17	10.98		14.33	
16	65.00	406.40	96.73	9.53	387.35	382.57	93.22	19.32			
16	75.00	406.40	111.61	11.13	384.15	379.37	108.43	17.33		20.68	
16	84.00	406.40	125.01	12.57	381.25	376.48	122.10	15.51		17.96	
16	109.00	406.40	162.21	16.66	373.08	368.30	160.13				
18 5/8	87.50	473.08	130.21	11.05	450.98	446.20	125.88	33.38		39.19	
20	94.00	508.00	139.89	11.13	485.75	480.97	136.30	21.32	27.76	24.86	
20	106.50	508.00	158.49	12.70	482.60	477.82	155.11	18.87	24.86	21.95	
20	133.00	508.00	197.93	16.13	475.74	470.97	195.62	13.61	18.42	15.97	

For more info please visit: <https://octgcasing.com/>